

Test Report No. AJFS1703000785FF Date: MAR.29, 2017 Page 1 of 4

SUZHOU HEAVEN WIND ENVIRONMENTAL TECHNOLOGY CO., LTD

QIUSHE INDUSTRIAL ZONE, TONGLI TOWN, WUJIANG, JIANGSU PROVINCE

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description: DISPOSABLE CUBICLE CURTAIN FABRIC

SGS Ref No.: AJHL1703002003FT

<u>Color</u>: PACIFIC BLUE <u>Density</u>: 120GSM

Composition: 100% POLYPROPYLENE

P.O. / Ref No.: 201703006

Style/Item No.: 3020

Supplier: SUZHOU HEAVEN WIND ENVIRONMENTAL TECHNOLOGY CO., LTD

Buyer: ALL OVER THE WORLD

Manufacturer: SUZHOU HEAVEN WIND ENVIRONMENTAL TECHNOLOGY CO., LTD

Country of Destination: ALL OVER THE WORLD

End Use Application: HOSPITALS

Addition Information: NON-WOVEN FABRIC

Test Requested:

Type C of BS 5867-2 :2008 Specification for Fabrics for curtains, drapes and window blinds – Part2: Flammability requirements and test method is based on BS EN ISO 15025: 2002.

Test Results: -- See attached sheet --

<u>Conclusion</u>: According to the test results, the submitted sample "As received" **meets** the requirements of Type C

of BS 5867-2:2008.

Test Period:

Sample Receiving Date : MAR.21, 2017

Test Performing Date : MAR.21, 2017 TO MAR.27, 2017

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch

Allen Zou

Technical Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at http://www.sg.com/en/Terms-and-Conditions.aspx and for electronic format documents subject to Terms and Conditions for Electronic Documents as a <a href="http://www.sg.com/en/Terms-and-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Conditions/Terms-en-Comment is devised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to it transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content o appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

1443, or email: CN.Doccheck@sgs.com
No.301, Sunlight Road, 2 Block, Sunlight Industry.Zone, Anj County, Zhejang Province, China 313300 t (多元72 501885 f (多元72 501885) www.sgsgroup.com.cn
中国 - 浙江 - 安吉县阳光工业园二区阳光大道301号 邮编:313300 t (多元72 501885 f (多元72 501885) e sgs.china@sgs.com



Test Report No. AJFS1703000785FF Date: MAR.29, 2017 Page 2 of 4

Sample details

| Sample description / Color | Disposable Cubicle Curtain Fabric / Pacific Blue |
|----------------------------|--|
| Area density | About 105 g/m ² |
| Size of sample | 200 mm×160 mm |
| | |

| Per-condition T: 20± 2 °C H: 65±5 % at least 24 h |
|---|
|---|

II. Test Conducted

This test is conducted accordance with Type C of BS 5867-2 :2008 Specification for Fabrics for curtains, drapes and window blinds – Part 2: Flammability requirements and test method is based on BS EN ISO 15025: 2002.

III. Test Results

Before any cleaning procedure

| The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, flame application time 5s) | Machine direction | | Cross direction | |
|--|-------------------|----------|-----------------|----------|
| | 1 (Face) | 2 (Back) | 1 (Face) | 2 (Back) |
| Lowest boundary of flame reached the vertical edge (Yes or No) | No | No | No | No |
| Lowest boundary of flame reached the top edge (Yes or No) | No | No | No | No |
| Hole reached the vertical edge (Yes or No) | No | No | No | No |
| Hole reached the top edge (Yes or No) | No | No | No | No |
| Flaming debris (Yes or No) | No | No | No | No |
| Duration of afterflame (s) | 0 | 0 | 0 | 0 |
| Duration of afterglow (s) | 0 | 0 | 0 | 0 |
| Max. vertical extent of hole (mm) | 106 | 110 | 99 | 102 |
| Max. horizontal extent of hole (mm) | 27 | 29 | 34 | 30 |

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not expensive parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (56-755) 8307

| No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anj County, Zhejiang Province, China 313300 t (多元2 50)885 f (多元2 50)885 www.sgsgroup.com.cn 中国 - 浙江 - 安吉县别光工业园二区阳光大道301号 邮编:313300 t (多元2 50)885 f (多元2



Test Report No. AJFS1703000785FF Date: MAR.29, 2017 Page 3 of 4

| The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, flame application time 15s) | Machine direction | | Cross direction | |
|---|-------------------|----------|-----------------|----------|
| | 1 (Face) | 2 (Back) | 1 (Face) | 2 (Back) |
| Lowest boundary of flame reached the vertical edge (Yes or No) | No | No | No | No |
| Lowest boundary of flame reached the top edge (Yes or No) | No | No | No | No |
| Hole reached the vertical edge (Yes or No) | No | No | No | No |
| Hole reached the top edge (Yes or No) | No | No | No | No |
| Flaming debris (Yes or No) | No | No | No | No |
| Duration of afterflame (s) | 0 | 0 | 0 | 0 |
| Duration of afterglow (s) | 0 | 0 | 0 | 0 |
| Max. vertical extent of hole (mm) | 116 | 120 | 134 | 137 |
| Max. horizontal extent of hole (mm) | 30 | 33 | 28 | 30 |

| The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, flame application time 20s) | Machine direction | | Cross direction | |
|---|-------------------|----------|-----------------|----------|
| | 1 (Face) | 2 (Back) | 1 (Face) | 2 (Back) |
| Lowest boundary of flame reached the vertical edge (Yes or No) | No | No | No | No |
| Lowest boundary of flame reached the top edge (Yes or No) | No | No | No | No |
| Hole reached the vertical edge (Yes or No) | No | No | No | No |
| Hole reached the top edge (Yes or No) | No | No | No | No |
| Flaming debris (Yes or No) | No | No | No | No |
| Duration of afterflame (s) | 0 | 0 | 0 | 0 |
| Duration of afterglow (s) | 0 | 0 | 0 | 0 |
| Max. vertical extent of hole (mm) | 133 | 129 | 138 | 133 |
| Max. horizontal extent of hole (mm) | 23 | 27 | 27 | 24 |

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document, aspx.attention is drawn to the limitation of the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exceed a particular transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307

1443. or email: CN.Doccheck@sqs.com

No. 301, Sunlight Road, 2 Blook, Sunlight Industry Zone, Anj County, Zhejiang Province, China 313300 t (多-572 50)885 f (多-572 50)8829 www.spsgroup.com.cn 中国 - 浙江 - 安吉县阳光工业园二区阳光大道301号 邮编:313300 t (多-572 50)885 f (多-572 50)8829 e sgs.china@sgs.com



Test Report No. AJFS1703000785FF Date: MAR.29, 2017 Page 4 of 4

| The test methods is as per BS EN ISO 15025:2002, Procedure "A" (surface ignition, flame application time 30s) | Machine direction | | Cross direction | |
|---|-------------------|----------|-----------------|----------|
| | 1 (Face) | 2 (Back) | 1 (Face) | 2 (Back) |
| Lowest boundary of flame reached the vertical edge (Yes or No) | No | No | No | No |
| Lowest boundary of flame reached the top edge (Yes or No) | No | No | No | No |
| Hole reached the vertical edge (Yes or No) | No | No | No | No |
| Hole reached the top edge (Yes or No) | No | No | No | No |
| Flaming debris (Yes or No) | No | No | No | No |
| Duration of afterflame (s) | 0 | 0 | 0 | 0 |
| Duration of afterglow (s) | 0 | 0 | 0 | 0 |
| Max. vertical extent of hole (mm) | 150 | 144 | 153 | 150 |
| Max. horizontal extent of hole (mm) | 28 | 25 | 26 | 29 |

Criteria:

No part of any hole nor any part of the lowest boundary of any flame shall reach the top edge or either vertical edge of the sample specimen and there shall be no separation of any flaming debris from any specimen, or if the mean afterflame or afterglow times exceed 2.5 s, the fabric shall be deemed not to comply with the requirements for type "C" of this British Standard.

Photo Appendix:



SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.assys.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents is a <a href="https://document.assys.attention.assys.assy

No. 301, Sunlight Road, 2 Book, Sunlight Industry Zone, Anji County, Zhejang Province, China 313300 t (85-572) 501825 f (85-572) 501825 www.spsgroup.com.cn 中国・浙江・安吉县和光工业国二区阳光大道301号 邮编:313300 t (85-572) 501825 f (85-572) 501825 e sgs.china@sgs.com